



Front View



Rear View



Features

- Intel® Atom™ J1900/ N2807 Processor
- DDR3L 1333 SODIMM x 2, Up to 16GB (J1900), DDR3L 1333 SODIMM x 1, Up to 4GB (N2807)
- Dual Independent Display: VGA + HDMI
- Rich IO Supported: USB 3.0 x 1, USB 2.0 x 4~7
- Compact Size, Low Power & Fanless Solution




Specifications

System	
CPU	Intel® Atom™ J1900 Processor (4C @ 2.00 GHz CPU, 688/854 MHz GFX, 10W TDP), Intel® Atom™ N2807 Processor (2C @ 1.58 GHz CPU, 313/750 MHz GFX, 4.3W TDP)
Chipset	—
System Memory	204-pin SODIMM x 2 up to 8 GB (for J1900) 204-pin SODIMM x 1 up to 4 GB (for N2807) DDR3L 1333 MHz, Non-ECC, un-buffered memory, Dual-channel memory architecture
I/O Chipset	Fintech 81866D
Display Interface	Chipset Intel® Graphics Media Accelerator
	DP VGA x 1, Up to 1920 x 1200 @60 Hz ; HDMI x 1, Up to 1920 x 1200 @60 Hz
Storage Devices	2.5" HDD, Full-Size Mini-Card (optional)
Network	LAN Realtek® PCIe Gb LAN 8111G x 1
I/O	
Front I/O	USB USB 2.0 port x 4
	Audio —
	Display VGA x 1
	Others On/Off Button x 1, Power LED + HD LED x 1, (COM port optional if not use VGA port)
Rear I/O	USB USB 3.0/2.0 port x 1, USB 2.0 port x 2
	Audio Line-out (green) x 1, Line-in (blue) x 1
	Display HDMI x 1
	LAN RJ-45 connector x 1
	Power DC Power x 1
Others RS-232 connector x 1	
Expansion	Mini PCIe Full-size Mini-Card (PCIe +USB or mSATA) + SIM Card (mSATA default) x 1, Half-size Mini-Card (PCIe +USB) x 1
	Storage Full-size Mini-Card slot (mSATA default) x 1, SATA3 (6.0Gb/s) x 1, SATA2 (3.0Gb/s) x 1, SATA power connector x 1
	Others RS-232 9-pin int. box header x 1, RS-232/422/485 9-pin box header x 1, 5-pin USB 2.0 header(p=2.00mm) x 2
Indicator	Front Power LED x 1, HDD Active LED x 1
	Rear —
Power	
Battery	Lithium battery
Power Requirement	DC: 12V
Mechanical	
Dimension (WxHxD)	8" x 8" x 1.75" (203.20mm x 203.20mm x 44.45mm)
VESA Mounting	Wallmount
Anti-Vibration	0.5 Grms/ 5~ 500Hz/ operation – HDD
Anti-Shock	10 G peak acceleration (11 msec. duration)
Environmental	
Operating temperature	32°F ~ 122°F (0°C ~ 50°C)
Certificate	CE & FCC Class A
Operating System	
MS Windows	Windows® 7 32/64-bit, Windows® 8.1 32/64-bit
Linux	Fedora

Dimension

Unit: mm



Ordering Information

Part Number	CPU	RAM Module	Display	Cooler	Storage	LAN	USB	Serial Port	Expansion Slot	Power	Mounting
ACS-1U01-BT4-1900-V10	J1900 2.42G/2M	—	VGA x 1 HDMI x 1	Fanless w/ CPU heatsink	2.5" HDD shelf, Full-Size Mini-Card (mSATA) x 1	GbE x 1	USB3 x 1 USB 2.0 x 7	RS-232 x 1, RS-232/422/485 x 1 (W/O VGA)	Half-size Mini-Card x 1 w/o SIM Slot	DC12V	wallmount

Packing List

- Wallmount Kit
- 2.5" HDD tray
- Product DVD
- ACS-1U01-BT4 (1U Chassis w/ EMB-BT4)

Optional Accessories

- **1702031802**
Power Cord (US & Taiwan Type)
- **1702031803**
Power Cord (European Type)
- **170203180B**
Power Cord (China Type)
- **170203180E**
Power Cord (Japanese Type)
- **1255300607**
60W Power Adapter