

## Industrial Serial RS232/RS485/RS422 Fiber Optic Modem

### Features

- ▶ Plug-and-play, hot pluggable
- ▶ **ST/SC/FC/LC optional**
- ▶ Extends Bi-directional RS-232/RS-485/RS-422 up to 2Km on MMF, 80Km on SMF
- ▶ EIA /TIA standard RS232/485/422, 0~2Mbps rate
- ▶ Serial data is fully transparent, baud rate is self-adaptive, no setting is required
- ▶ The high speed serial data can be used for DMX512 communication in Stage Lighting Control
- ▶ Support DIN-Rail & Wall-mount installation.
- ▶ Built-in surge and static protection
- ▶ Diagnostic and unit indicator LEDs
- ▶ Environmentally Hardened -40° C to 75° C (-40° F to 176° F) operating temperature



### Overview

GIS 39SRI series is an industrial grade RS232/RS485/RS422 to fiber optic converter which converts a standard RS232/RS485/RS422 signal to a fiber optic link as to extend the signal up to 2Km on multimode fiber and 80Km on single mode fiber. The use of optical fiber communication solves the problems of electromagnetic interference, ground ring interference and lightning damage. It greatly improves the reliability, security and confidentiality of data communication, and can be widely used in various industrial control, process control, Stage Lighting Control and traffic control occasions.

### Application



## Technical Indexes

<b>Model</b>	GIS 39SRI Series
<b>Fiber Connector</b>	ST/SC/FC/LC optional
<b>Fiber Distance</b>	50/125um MMF: 2Km, 62.5/125um MMF: 5Km, 9/125 SMF:20/40/60/80Km
<b>Serial Interface</b>	Industrial Terminal
<b>Signal Ports</b>	1Ch RS232 - 1Mbps 1Ch R485 - 1Mbps 2Ch RS485H- 2Mbps 2Ch RS485H can be grouped into 1Ch High Speed RS422
<b>Standard</b>	EIA /TIA RS232/485/422
<b>Serial Distance</b>	RS232: 15 meters, RS485/422: 1000 meters
<b>Rate</b>	Max 2Mbps
<b>RS-232</b>	TXD, RXD, GND - Bi-directional
<b>RS-485</b>	D+, D-, GND - Bi-directional
<b>Power Supply</b>	DC12~48V
<b>Power rate</b>	<5W
<b>Static protection</b>	15KV electric static discharge (ESD) protection
<b>Surge protection</b>	1500W/sec surge protection
<b>Operation Temperature</b>	-25°C to +75°C
<b>Storage Temperature</b>	-40°C to +85°C
<b>Storage Humidity</b>	5%~90% non-condescending
<b>Dimensions</b>	95(L)*70(W)*29(H) mm
<b>Weight</b>	0.25kg/pcs

## Ordering Information

Model	Description
GIS 39SRI-SFP	Industrial Serial RS232/RS485/RS422 with SFP port
GIS 39SRI-SCMM	Industrial Serial RS232/RS485/RS422 , <b>SC</b> MM 850nm, <b>550m</b>
GIS 39SRISCMM-2	Industrial Serial RS232/RS485/RS422 , <b>SC</b> MM 1310nm, <b>2km</b>
GIS 39SRI-SC20	Industrial Serial RS232/RS485/RS422 , <b>SC</b> SM 1310nm, <b>20km</b>
GIS 39SRI-STMM	Industrial Serial RS232/RS485/RS422 , <b>ST</b> MM 850nm, <b>550m</b>
GIS 39SRI-STMM-2	Industrial Serial RS232/RS485/RS422 , <b>ST</b> MM 1310nm, <b>2km</b>
GIS 39SRI-ST20	Industrial Serial RS232/RS485/RS422 , <b>ST</b> SM 1310nm, <b>20km</b>
Mounting Options	► Default DIN-Rail Bracket installed, Wall Mount Bracket is included.
Power Options	► Power Supply is to be purchased separately