

PB-9250J Series

Standalone Intelligent Supercapacitor-based Uninterruptible Power Backup Module



Key Features

- · Universal standalone power backup module compatible with all box-PCs
- · Supercapacitor-based, -25 to 65°C wide temperature operation
- 9250 watt-second energy capacity
- · Maximum 180W output power for the connected back-end system
- · Up to 10 years lifespan, and 500,000 charging/ discharging cycles
- Patented CAP energy management technology*
 - Extends back-up time in the event of an unforeseen power outage
 - Monitors energy and power consumption to extend operation time for safe system shutdown
- Versatile operating mode
- Normal backup mode
- Ignition control mode for standard box-PC and in-vehicle controller
- UltraCAP energy/ lifespan configuration
- · EN50155 certificate

*R.O.C Patent No. 1598820

Introduction

PB-9250J-SA is a standalone power backup module that can protect your box-PC against power outages. Utilizing state-of-the-art supercapacitor technology, it can operate in harsh environments from -25 to 65°C, and have extremely high durability lasting up to 10 years.

PB-9250J-SA is composed of eight 370F/ 3.0V supercapacitors, which offers 3.3 times longer lifespan than its 2.7V counterpart, and stores 9250 watt-second energy to offer extra extended operation time to backup your system. Thanks to Neousys' patented CAP energy management technology, It can reliably supply 180W power to the back-end system and automatically manage boot and shutdown without installing additional drivers/ software. In addition to UPS-like power backup mode, it also offers two advanced ignition control modes for in-vehicle usage. PB-9250J-SA can work with either standard box-PC or in-vehicle controller to provide stable power supply and execute user-configurable power-on/ power-off delay according to IGN signal input.

Featuring various modes, automatic shutdown control and up to 180W output power, PB-9250J-SA can work with most off-the-shelf box-PCs. And with properties such as maintenance-free energy storage and uninterruptible power supply, PB-9250J-SA can prevent data loss for the connected back-end system during power outage in harsh industrial environments!



Specifications

Supercapacitor Configuration		
Composition	8x 370F, 3.0V supercapacitors	
Capacity	9250 watt-second	
Expected lifespan	>10 years @ 25°C with 9250 ws capacity* 76,000 hours @ 35°C with 9250 ws capacity* 34,000 hours @ 45°C with 9250 ws capacity* 15,000 hours @ 55°C with 9250 ws capacity* 7,200 hours @ 65°C with 9250 ws capacity* 7,200 hours @ 85°C with 9250 ws capacity* 7,200 hours @ 85°C with reduced 6525 ws capacity* Expected lifespan is 2.2x when configured as 7820 watt-second energy capacity, or 4.8x when configured as 6525 watt-second energy capacity.	
Lifecycle	500,000 charging/ discharging cycles*	
Power Specification		
Input Voltage	12~35 VDC	
Input Connector	1x 3-pin pluggable terminal block (V+, GND, IGN_IN)	
Output Voltage	Charge mode: DC_IN bypass (DC_OUT = DC_IN) Discharge mode: 12 or 24V software-configurable	
Output Power	Maximum 180W output**	
Output Connector	1x 3-pin pluggable terminal block (V+, GND, IGN_OUT)	

I/O Interface	
COM Port	1x DB9 for 3-wire RS-232
Iso. DIO	1x 10-pin pluggable terminal block for - PWR_BTN# output - SYS_STAT input
Mechanical	
Dimension	80 mm (W) x 128 mm (D) x 175 mm (H)
Weight	1.7 kg
Mounting	DIN-rail mounting and wall-mounting
Environmenta	I
Operating Temperature	-25°C \sim 65°C -40°C \sim 85°C with reduced energy capacity
Storage Temperature	-40°C ~ 85°C
Vibration	Operating, MIL-STD-810G, Method 514.6, Category 4
Shock	Operating, MIL-STD-810G, Method 516.6, Procedure I, Table 516.6 II
EMC	EN50155 CE/FCC Class A, according to EN 55032 & EN 55035
* Once the rated lifetim	ne or cycle life has been reached, the capacity of supercapacitor may decrease up to 30%

and ESR may increase up to 100% from initial values.

Ordering Information

Model No.	Product Description
PB-9250J-SA	Standalone intelligent supercapacitor-base power backup module with 9250 W·s energy capacity

^{**} Backup time for uninterruptible operation may be reduced when sustaining a back-end system with high