# HPC-7484

#### 4U Rackmount / Tower Chassis for EATX/ATX/MicroATX Motherboard with 8 Hot Swap Drive Trays



#### **Features**

- Supports EATX/ATX/MicroATX motherboard
- Shock-resistant disk drive bay provides eight hot-swap 3.5" or 2.5" SAS/SATA disk trays, one slim optical disk drive, and one 2.5" internal drive space
- Supports 80plus single high watt power supply (700W/1200W)
- Supports up to seven FH/FL expansion slots
- LED indicators and alarm notification for system fault detection
- Easy maintenance system fans


# Quiet Specifications

# C€ FCC

-			
		External	Internal
Drive Bay	Slim Optical Drive	1	-
DIIVE Day	2.5"	-	1
	Hot Swap	8 (2.5"/3.5" SASIII/SATAIII HDD)	
Cooling	Fan*	2 (120mm(L) x 120mm(W) x 25mm(T)/150cfm)	
Cooling	Air Filter	Yes	
Front I/O Interface	USB 3.0	ISB 3.0 2	
Miscellaneous	LED Indicators	Power, HDD, Information, LAN1, LAN2	
IVIISCEITAITEOUS	Rear Panel	Five 9-pin D-Sub and one 68-pin SCSI openings	
		Operating	Non-Operating
	Temperature	0 ~ 40 °C (32 ~ 104 °F)	-40 ~ 70 °C (-40 ~ 156 °F)
Environment	Humidity	10 ~ 95% @ 40 °C, non-condensing	10 ~ 95% @ 60 °C, non-condensing
	Vibration (5 ~ 500 Hz)	1 Grms	2 G
	Shock	10 G (with 11 ms duration, half sine wave)	
Physical Characteristics	Dimensions (W x H x D)	426 x 177 x 630mm (16.7" x 7.0" x 24.8")	
Physical Undidulensilus	Weight	19.0 Kg (41.85 lb)	

## **Front View**

## **Inside View**





With 700W single power supply




With 1200W single power supply

AD\ANTECH Server Chassis

All product specifications are subject to change without notice.

Last updated: 26-Dec-2018

#### HPC-7484



#### **Ordering Information**

 Part Number
 D

 HPC-7484-70ZX
 W

 HPC-7484-12ZX
 W

**Description** With 700W single PSU With 1200W single PSU

## **Packing List**

Part Number	Description	
9662132020E	Black mobile HDD tray (pre-installed in the chassis)	
1990021256T000	Door filter (pre-installed in the chassis)	

#### **Optional Accessories**

Cable Request for Optional Device	Part Number	Description	Quality
Slim ODD power cable	96CB-SATAPOWER-6P2	SATA power wire 6-pin to big 4-pin (for slim ODD)	1
MB without RAID card	1700029405-01	M cable SAS 36P/SATA 7P*4+1*5P-2.54 55cm	2
MB with SAS2 RAID card	1700025439-01	Internal SAS cable(6G) SFF-8643 to SFF-8087, 60cm	2
MB with SAS3 RAID card	1700025064-01	Internal SAS cable(12G) SFF-8643 to SFF-8643, 60cm	2

Optional Device	Part Number	Description	Quality
Slim ODD	Refer to the P-trade web site	slim optical disk drive	1
With 3x GTX cards	1750008774-01	replace system fan A with 120mmx120mmx38mm fan as installing 3 x GTX cards $^{\ast}$	1
Rail kit	9680006905	26" Slide Rail	1

\* NOTE 1. disassemble the fan guard from original system fan A, then assemble the fan guard to 1750008774-01.

\* NOTE 2. need 1750008774-01 as installing 3 x GTX cards only, not support 1 or 2 GTX cards, and GTX cards must be founders edtion.